


# Ultra-Lath Plus® 1/4" Self-furred Yellow Plastic Lath



## DESCRIPTION

Ultra-Lath Plus® non-metallic lath is the non-rusting alternative to metal laths.

Unaffected by salt, moisture and chemicals, heavy-duty Ultra-Lath Plus is 1/4" self-furred for improved keying. It is compatible with all cement-based products.



Section

Safe and easier to use than metal laths.

Lower installed costs.

Patent pending

## USES

Stucco - Three coat interior or exterior stucco applications

**\*Approved for Vertical and Horizontal applications**

Stone Veneer Systems - Interior or exterior applications

Hardscapes - Three dimensional shaping in interior or exterior hardscape projects

## FEATURES

**Non-metallic**  
(High-density polyethylene)

**1/4" (6 mm) self-furred**

**Non-directional**

**Safer on hands**

**Lightweight**

**Non-conductive**

**Available in sheets, rolls, strips**

Paper-backed sheets

3, 4, 6, 8 inch Strip-Lath® strips

## BENEFITS

Non-rusting, Non-corroding – Unaffected by sand, chemicals in cementitious stucco

Improved keying of stucco

Installs horizontal or vertical  
Easy to shape, won't crimp or kink

No sharp edges or ends

Labor-savings  
Easy to handle, cuts with utility knife

Does not affect WiFi, wireless transmissions

Sheets available with and without paper backing

Combine paper, lath processes, saving on labor

Bridge dissimilar building materials

## PACKAGING

Type / Catalog #	Description/Dimensions	Packaging	Pallet Qty
Sheets, paper-backed <b>PDM2796PB-25</b>	27" x 96" (686 mm x 2.4 m) Backing: Asphalt impregnated Type 1, Grade D, Style 2 paper with standard offset	10 sheets/bundle (180 sq ft/bundle)	20 bundles/pallet (3,600 sq ft/pallet)
Sheets <b>PDM2796-25</b>	27" x 96" (686 mm x 2.4 m)	10 per bundle (180 sq ft/bundle)	20 bundles/pallet (3,600 sq ft/pallet)
Rolls <b>PDMR-25</b>	27" x 75' (686 mm x 22.9 m)	168 ft/roll	18 rolls/pallet (3,024 sq ft/pallet)
Strip-Lath® strips <b>PDM3-25</b>	3" x 96" (76 mm x 2.4 m)	50 pieces per box	---
Strip-Lath® strips <b>PDM4-25</b>	4" x 96" (102 mm x 2.4 m)	50 pieces per box	---
Strip-Lath® strips <b>PDM6-25</b>	6" x 96" (152 mm x 2.4 m)	50 pieces per box	---
Strip-Lath® strips <b>PDM8-25</b>	8" x 96" (203 mm x 2.4 m)	50 pieces per box	---

## COMPLIANCE, TEST DATA

- **Florida Building Code**, Building (FBC), including HVHZ and Florida Building Code, Residential (FRC), including HVHZ
- Meets **ASTM C1063, C1764, C1780, C1787, C1788 and C1861**, and requirements for Non Metallic Plaster Bases as set forth in ASTM C926
- Meets Non Metallic lath requirements (**ASTM C1788**) set forth in Masonry Veneer Manufacturers Association Installation Guide for Adhered Manufactured Stone Veneer (5th Ed)
- Paper meets **Federal Specification UU-B-790A**; Style 1, Grade D, Style 2
- Recognized by **IAPMO Uniform Evaluation Services** report #0284 (revised April, 2019) for use in vertical or horizontal applications
- Passed **NFPA285** fire test for multi-story assemblies – Approved for Type 1 to 5 construction
- Third party tested by **Intertek Testing Services** for freeze/thaw, transverse load, alkali resistance and compressive and flexural strength
- Third party tested by **Fenestration Testing Laboratory** for Miami-Dade County code approvals, test protocols PA201, PA202, PA203



Meets ASTM C1063,  
C1764, C1780, C1787,  
C1788, C1861



UER #0284

**PASSES NFPA 285 FIRE TEST**

## LIMITATIONS

Not recommended for use on open framing

Since 1969  
**PLASTIC PC**  
**COMPONENTS inc.**

[www.plasticcomponents.com](http://www.plasticcomponents.com)

9051 NW 97th Terrace • Miami, FL 33178 • 305.885.0561 • Fax 305.887.2452 • 800.327.7077