REVEALS + MOLDINGS

FRY REGLET

ENGINEERED PRODUCT SYSTEMS

REVEALS + MOLDINGS PRODUCT BROCHURE

2ND EDITION

CONTENTS

D Drywall Reveals & Moldings

DA REVEALS

- **DA.1** Reveal
- **DA.2** "F" Reveal
- **DA.3** "Snap-In" Reveal
- **DA.4** Base
- **DA.5** Field
- **DA.6** Outside Corner
- **DA.7** "Z" Reveal
- **DA.8** Reveal Base
- **DA.9** Step Trim
- **DA.10** "V" Reveal
- **DA.11** Reverse "V" Reveal
- **DA.12** "W" Reveal
- **DA.13** Reveal/Picture Hanger
- **DA.14** Reveal Channel Screed/Plaster and Stucco Control Joint
- **DA.15** "F" Reveal
- **DA.16** "T" Molding
- **DA.17** "X" Molding
- **DA.18** "W" Molding

DB EXPANSION JOINTS

- **DB.1** Drywall Expansion Joint

DC TRIMS

- **DC.1** Corner Trim
- **DC.2** "L" Trim Molding
- **DC.3** Edge Trim
- **DC.4** Edge Trim
- **DC.5** Radius Corner Trim
- **DC.6** Pocket Trim
- **DC.7** "J" Molding
- **DC.8** Drywall Molding End Closure
- **DC.9** Top Track
- **DC.10** Ceiling Trim
- **DC.11** Protruding Edge
- **DC.12** 30° / 45° Angle Trim
- **DC.13** Wall Angle

DD CORNERS

- **DD.1** Stepped Outside Corner / Drywall Corner Reveal
- **DD.2** Multiple Stepped Outside Corner
- **DD.3** Beveled Corner
- **DD.4** Curved Inside Corner
- **DD.5** Curved Outside Corner
- **DA.6** Bullnose

DE COLUMN COLLARS + RINGS

- **DE.1** Column Collar
- **DE.2** Reveal Column Ring
- **DE.3** Wall Angle Column Ring

DF ACOUSTICAL

- **DF.1** "W" Reveal Molding
- **DF.2** Drywall/Acoustical Reveal
- **DF.3** Acoustical Ceiling Trim
- **DF.4** Acoustical Molding
- **DF.5** "W" Acoustical Reveal
- **DF.6** "F" Acoustical Reveal
- **DF.7** "J" Acoustical Trim

DG SPECIAL SECTIONS

- **DG.1** Special Sections
- **DG.2** Contemporary Reveal

DH GLAZING TRACK

- **DH.1** Glazing Track / Drywall Ceiling Track
- **DH.2** Acoustical Ceiling Tract / Drywall Acoustical Ceiling

DI INTEGRATED FUNCTION REVEAL

- **DI.1** Reveal Rail
  Chartrail Insert
  Hook Insert

DJ INSTALLATION

- **DJ.1** Installation Guide
- **DJ.2** Installation Guide
- **DJ.3** Installation Guide
- **DJ.4** Venting Information

D Drywall Moldings

GUIDE SPECIFICATION

Where indicated on drawings, Fry Reglet reveals and moldings, as manufactured by Fry Reglet Corporation, shall be installed. Fry Reglet aluminum reveals and moldings shall be extruded alloy 6063 T5, with chemical conversion coating, primed finish, clear anodized or other specified finish. Refer to finish section.

DA.1	DA.2	DA.3	DA.4	DA.5
REVEAL	"F" REVEAL	"SNAP-IN" REVEAL	BASE	FIELD

DA.6	DA.7	DA.8	DA.9	DA.10
OUTSIDE CORNER	"Z" REVEAL	REVEAL BASE	STEP TRIM	"V" REVEAL
				

DA.11	DA.12	DA.13	DA.14	DA.15
REVERSE "V" REVEAL	"W" REVEAL	REVEAL/ PICTURE HANGER	REVEAL CHANNEL SCREED/ PLASTER AND STUCCO CONTROL JOINT	"F" REVEAL
				

DA.16	DA.17	DA.18	DB.1	DC.1
"T" MOLDING	"X" MOLDING	"W" MOLDING	DRYWALL EXPANSION JOINT	CORNER TRIM
				

DC.2	DC.3	DC.4	DC.5	DC.6
"L" TRIM MOLDING	EDGE TRIM	EDGE TRIM	RADIUS CORNER TRIM	POCKET TRIM

SHAPE FINDER INDEX

D Drywall Moldings

DC.7	DC.8	DC.9	DC.10	DC.11
"J" MOLDING	DRYWALL MOLDING END CLOSURE	TOP TRACK	CEILING TRIM	PROTRUDING EDGE
				

DC.12	DC.13	DD.1	DD.2	DD.3
30° / 45° ANGLE TRIM	WALL ANGLE TRIM	STEPPED OUTSIDE CORNER	BEVELED CORNER	MULTIPLE STEPPED OUTSIDE CORNER

DD.4	DD.5	DD.6	DE.1	DE.2
CURVED INSIDE CORNER	CURVED OUTSIDE CORNER	BULLNOSE	COLUMN COLLAR	REVEAL COLUMN RING
				

DE.3	DF.1	DF.2	DF.3	DF.4
WALL ANGLE COLUMN RING	"W" REVEAL MOLDING	DRYWALL - ACOUSTICAL REVEAL	ACOUSTICAL CEILING TRIM	ACOUSTICAL MOLDING
				

DF.5	DF.6	DF.7	DG.1	DG.2
"W" ACOUSTICAL REVEAL	"F" ACOUSTICAL REVEAL	"F" ACOUSTICAL TRIM	"F" ACOUSTICAL REVEAL	"F" ACOUSTICAL TRIM
				

DH.1	DH.2	DI.1
GLAZING TRACK	ACOUSTICAL CEILING TRACK	INTEGRATED FUNCTION REVEAL
		

DA.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
1/4"	1/4"	DRM-25-25	--
1/2"	1/8"	DRM-50-125	--
1/2"	1/4"	DRM-50-25	--
1/2"	3/8"	DRM-50-375	--
1/2"	1/2"	DRM-50-50	DRM-50-V-50
1/2"	5/8"	DRM-50-625	DRM-50-V-625
1/2"	3/4"	DRM-50-75	DRM-50-V-75
1/2"	1"	DRM-50-100	DRM-50-V-100
1/2"	1 1/2"	DRM-50-150	DRM-50-V-150
1/2"	2"	DRM-50-200	DRM-50-V-200
1/2"	2 1/2"	DRM-50-250	DRM-50-V-250
1/2"	3"	DRM-50-300	DRM-50-V-300
1/2"	4"	DRM-50-400	DRM-50-V-400
5/8"	1/4"	DRM-625-25	--
5/8"	3/8"	DRM-625-375	--
5/8"	1/2"	DRM-625-50	DRM-625-V-50
5/8"	5/8"	DRM-625-625	DRM-625-V-625
5/8"	3/4"	DRM-625-75	DRM-625-V-75
5/8"	1"	DRM-625-100	DRM-625-V-100
5/8"	1 1/4"	DRM-625-1250	DRM-625-V-1250
5/8"	1 1/2"	DRM-625-150	DRM-625-V-150
5/8"	2"	DRM-625-200	DRM-625-V-200
5/8"	2 1/2"	DRM-625-250	DRM-625-V-250
5/8"	3"	DRM-625-300	DRM-625-V-300
5/8"	4"	DRM-625-400	DRM-625-V-400
5/8"	6"	DRM-625-600	DRM-625-V-600



DA.2 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

"F" REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
1/2"	1/8"	DRMF-50-125	--
1/2"	1/4"	DRMF-50-25	--
1/2"	3/8"	DRMF-50-375	--
1/2"	1/2"	DRMF-50-50	DRMF-50-V-50
1/2"	5/8"	DRMF-50-625	DRMF-50-V-625
1/2"	3/4"	DRMF-50-75	DRMF-50-V-75
1/2"	1"	DRMF-50-100	DRMF-50-V-100
5/8"	3/8"	DRMF-625-375	--
5/8"	1/2"	DRMF-625-50	DRMF-625-V-50
5/8"	5/8"	DRMF-625-625	DRMF-625-V-625
5/8"	3/4"	DRMF-625-75	DRMF-625-V-75
5/8"	1"	DRMF-625-100	DRMF-625-V-100
5/8"	1 1/2"	DRMF-625-150	DRMF-625-V-150
5/8"	2"	DRMF-625-200	DRMF-625-V-200
5/8"	3"	DRMF-625-300	DRMF-625-V-300



DA.3 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

"SNAP-IN" REVEAL

DIM. A REVEAL WIDTH	NUMBER
3/8"*	DRM-SNAP-IN-375
1/2"**	DRM-SNAP-IN-50
5/8"***	DRM-SNAP-IN-625

*Snap-In fits following profiles:
DRM-50-50, DRM-625-50, DRMF-50-50, DRMF-625-50
**Snap-In fits following profiles:
DRM-50-625, DRM-625-625, DRMF-50-625, DRMF-625-625
***Snap-In fits following profiles:
DRM-50-75, DRM-625-75, DRMF-50-75, DRMF-625-75



DA.4 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

WALL COVERING TRIMS

WCTBT125-217 (BASE & TERMINATION)



WCTBT125-217



DA.5 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

WCTF125-217 (FIELD)



WCTF125-217



DA.6 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

WCTOSC (OUTSIDE CORNER)



WCTOSC



DA.7 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"Z" REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
1/4"	1/4"	DRMZ-25-25	--
1/2"	1/8"	DRMZ-50-125	--
1/2"	1/4"	DRMZ-50-25	--
1/2"	3/8"	DRMZ-50-375	--
1/2"	1/2"	DRMZ-50-50	DRMZ-50-V-50
1/2"	5/8"	DRMZ-50-625	DRMZ-50-V-625
1/2"	3/4"	DRMZ-50-75	DRMZ-50-V-75
1/2"	1"	DRMZ-50-100	DRMZ-50-V-100
1/2"	1 1/2"	DRMZ-50-150	DRMZ-50-V-150
1/2"	2"	DRMZ-50-200	DRMZ-50-V-200
5/8"	1/4"	DRMZ-625-25	--
5/8"	3/8"	DRMZ-625-375	--
5/8"	1/2"	DRMZ-625-50	DRMZ-625-V-50
5/8"	5/8"	DRMZ-625-625	DRMZ-625-V-625
5/8"	3/4"	DRMZ-625-75	DRMZ-625-V-75
5/8"	1"	DRMZ-625-100	DRMZ-625-V-100
5/8"	1 1/4"	DRMZ-625-1250	DRMZ-625-V-1250
5/8"	2"	DRMZ-625-200	DRMZ-625-V-200
1"	1"	DRMZ-100-100	DRMZ-100-V-100



DA.8 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

REVEAL BASE

DIM. A REVEAL DEPTH	DIM. B REVEAL HEIGHT	NUMBER
1/2"	4"	DRMB-50-400
5/8"	2 1/2"	DRMB-625-250
5/8"	3"	DRMB-625-300
5/8"	4"	DRMB-625-400
5/8"	6"	DRMB-625-600



DA.9 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

STEP TRIM

DIM. A STEP SIZE	NUMBER
1/2"	DMST-50-50
5/8"	DMST-625-625



DA.10 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"V" REVEAL

DIM. A REVEAL WIDTH	DIM. B REVEAL DEPTH	NUMBER
1/4"	1/4"	DRMV-25
3/4"	1/2"	DRMV-75
1"	1/2"	DRMV-100



DA.11 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

REVERSE "V" REVEAL MOLDING

REVEAL WIDTH	NUMBER
1"	DRMVR-100



DA.12 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"W" REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER
1/2"	1/2"	DRWT-50-50
3/4"	3/4"	DRWT-75-75
2"	2"	DRWT-200-200



DA.13 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

REVEAL/ PICTURE HANGER

REVEAL WIDTH	NUMBER
3/4"	DRMH-50

*Hanger clips (DRMH-50 insert) sold separately.
Note: Maximum capacity per hanger clip is 75 pounds.
Not to exceed 4 clips per 10ft. peice



DA.14

PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

REVEAL CHANNEL SCREED/PLASTER AND STUCCO CONTROL JOINT

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
1/2"	1/2"	DCS-50-50	DCS-50-V-50
1/2"	3/4"	DCS-50-75	DCS-50-V-75
1/2"	1"	DCS-50-100	DCS-50-V-100
1/2"	1 1/2"	DCS-50-150	DCS-50-V-150
1/2"	2"	DCS-50-200	DCS-50-V-200
1/2"	3"	DCS-50-300	DCS-50-V-300
1/2"	4"	DCS-50-400	DCS-50-V-400
5/8"	1/2"	DCS-625-50	DCS-625-V-50
5/8"	3/4"	DCS-625-75	DCS-625-V-75
5/8"	1"	DCS-625-100	DCS-625-V-100
5/8"	1 1/2"	DCS-625-150	DCS-625-V-150
5/8"	2"	DCS-625-200	DCS-625-V-200
5/8"	2 1/2"	DCS-625-250	DCS-625-V-250
5/8"	3"	DCS-625-300	DCS-625-V-300
5/8"	4"	DCS-625-400	DCS-625-V-400
5/8"	6"	DCS-625-600	DCS-625-V-600



DA.15

PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

"F" REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
1/2"	3/4"	FDM-50-75	FDM-50-V-75
5/8"	1/2"	FDM-625-50	FDM-625-V-50
5/8"	3/4"	FDM-625-75	FDM-625-V-75
5/8"	1"	FDM-625-100	FDM-625-V-100
5/8"	1 1/2"	FDM-625-150	FDM-625-V-150
5/8"	2 1/2"	FDM-625-250	FDM-625-V-250
5/8"	3"	FDM-625-300	FDM-625-V-300



DA.16 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"T" MOLDING

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
1/2"	1/2"	TDM-50-50	TDM-50-V-50
1/2"	3/4"	TDM-50-75	TDM-50-V-75
1/2"	1 1/8"	TDM-50-1125	TDM-50-V-1125
1/2"	1 1/2"	TDM-50-150	TDM-50-V-150
5/8"	1/2"	TDM-625-50	TDM-625-V-50
5/8"	3/4"	TDM-625-75	TDM-625-V-75
5/8"	1 1/8"	TDM-625-1125	TDM-625-V-1125



DA.17 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"X" MOLDING

DIM A.	NUMBER
1/2"	XDM-50-50
5/8"	XDM-625-625



DA.18 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"W" MOLDING

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	DIM. C REVEAL DEPTH	NUMBER	
			NON-VENTED	VENTED
1/2"	1/2"	5/8"	WDM-50-50-625	--
1/2"	3/4"	1"	WDM-50-75	WDM-50-V-75
5/8"	3/4"	1"	WDM-625-75	WDM-625-V-75
3/4"	3/4"	5/8"	WRM-75-75-625	WRM-75-V-75-625



DB.1 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

DRYWALL EXPANSION JOINT

GROUND	DIM. A REVEAL WIDTH	NUMBER	
		2-PIECE	3-PIECE
1/2"	1/4"	DRM-50-25 2-PC	–
1/2"	1/2"	DRM-50-50 2-PC	DRM-50-50 3-PC
1/2"	3/4"	DRM-50-75 2-PC	DRM-50-75 3-PC
1/2"	1"	–	DRM-50-100 3-PC
1/2"	1 1/2"	DRM-50-150 2-PC	DRM-50-150 3-PC

2-PIECE ONE COMPRESSION SEAL



3-PIECE TWO COMPRESSION SEALS



DC.1 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

CORNER TRIM

DIM A. EXPOSED CORNER	NUMBER
3/8"	DMCT-375
1 1/4"	DMCT-1250



DC.2 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"L" TRIM MOLDING

DIM. A TRIM DEPTH	NUMBER
1/2"	DRML-50
5/8"	DRML-625
3/4"	DRML-75
1"	DRML-100
1 1/4"	DRML-1250
1 1/2"	DRML-150
1 5/8"	DRML-1625
2"	DRML-200
2 1/2"	DRML-250
3"	DRML-300



DC.3 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

EDGE TRIM

DIM A. TRIM DEPTH	NUMBER
1/2" ●	DMET-50
1" ■	DMET-100
1 1/2" ▲	DMET-150

● Additional layer of 1/2" drywall
■ Two additional layers of 1/2" drywall
▲ Three additional layers of 1/2" drywall

DMET-100, DMET-150



DMET-50





DC.4 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

EDGE TRIM

DIM A. TRIM DEPTH	NUMBER
1/2" ●	DRME-50
5/8" ■	DRME-625
1 1/4"	DRME-1250

● Additional layer of 1/2" drywall
■ Two additional layers of 5/8" drywall



DC.5 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

RADIUS CORNER TRIM

DIM A.	NUMBER
1/2"	RCT-50



DC.6 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

POCKET TRIM

WIDTH OF TILE SUPPORT	NUMBER
3/4"	DMPT-75



DC.7 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

"J" MOLDING

DIM A.	DIM B.	DIM C.	NUMBER
1/2"	3/16"	1 1/16"	JDM-50
5/8"	3/16"	1 1/16"	JDM-625



"J" Molding

DC.8 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

DRYWALL MOLDING END CLOSURE

DIM. A*	NUMBER
2"	DMEC-200
3 1/2"	DMEC-3500
3 3/4"	DMEC-3750
4 5/8"	DMEC-4625
4 7/8"	DMEC-4875
7 1/4"	DMEC-7250



DC.9 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

TOP TRACK

REVEAL DEPTH DRYWALL THICKNESS)	DIM. A STUD WIDTH	NUMBER
5/8"	3 5/8"	DMTT-625-3750



DC.10 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

CEILING TRIM

DIM. A	DIM. B	NUMBER
1/2"	1/2"	DRMCT-50-50
5/8"	3/4"	DRMCT-625-75
5/8"	1"	DRMCT-625-100



DC.11 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

PROTRUDING EDGE PROFILES

DIM. A	DIM. B	NUMBER
3/8"	N/A	DRMPET-375
1"	N/A	DRMPET-100
1"	3/4"	DRMPWR-100-75
1"	1"	DRMPCR-100-100

DRMPET-375



DRMPET-100



DRMPWR-100-75



DRMPCR-100-100



DRMPET-375



DRMPET-100



DRMPWR-100-75



DRMPCR-100-100



DC.12 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

30° / 45° ANGLE TRIM

DIM A	DIM B	NUMBER
30°	2 7/8"	DMAT-30-500
45°	4 1/8"	DMAT-45-500



DC.13 PRODUCT DETAIL CROSS SECTION / INSTALLATION DETAIL

WALL ANGLE

DIM A	DIM B	NUMBER
3/4"	1"	WA75100
1"	2"	WA100200



DD.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

STEPPED OUTSIDE CORNER | DRYWALL CORNER REVEAL

DIM. A NOTCH WIDTH	DIM. B NOTCH HEIGHT	NUMBER
1/2"	1/2"	DRMW 50-50
1/2"	1 1/2"	DRMW 50-150
5/8"	5/8"	DRMW 625-625
1 1/2"	1 1/2"	DRMW 150-150



DD.2 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

MULTIPLE STEPPED OUTSIDE CORNER

DIM. A	NUMBER
5/8"	DMOS-625
1 1/2"	DMOS-150



DD.3 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

BEVELED CORNER

BEVEL WIDTH	NUMBER
3/4"	DMBC-75



DD.4 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

CURVED INSIDE CORNER

"R" RADIUS	DIM A	NUMBER
3/4"	1 1/4"	DRMC-IS-75
1"	1 9/16"	DRMC-IS-100
1 1/2"	2 5/16"	DRMC-IS-150
2"	2 7/8"	DRMC-IS-200
3"	4 1/4"	DRMC-IS-300
4"	5 5/8"	DRMC-IS-400
6"	8 7/16"	DRMC-IS-600



DD.5 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

CURVED OUTSIDE CORNER

"R" RADIUS	DIM A	NUMBER
5/8"	1"	DRMC-OS-625
3/4"	1"	DRMC-OS-75
1"	1 3/8"	DRMC-OS-100
1 1/2"	2 1/8"	DRMC-OS-150
2"	2 3/4"	DRMC-OS-200
2 1/2"	3 9/16"	DRMC-OS-250
3"	4 3/16"	DRMC-OS-300
4"	5 11/16"	DRMC-OS-400



*Contact Fry Reglet for installation recommendations

DD.6 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

BULLNOSE

DIM. A DRYWALL THICKNESS	DIM. B STUD WIDTH	NUMBER
5/8"	2 1/2"	DBN-625-250
5/8"	3 5/8"	DBN-625-3625



COLUMN COLLAR

DRYWALL





ACOUSTICAL/DRYWALL





PLASTER





Column covers are manufactured to fit specific columns from 10" to 48" in diameter.

USAGE

Fry Reglet Column Collar provides a functional, attractive trim creating a reveal at column/ceiling joint. PVC spacer insures an attractive appearance and no light leaks. Fabricated to fit specific column sizes. Tightens in place with a turnbuckle and stainless steel metal band. Available with white or dark bronze PVC spacer. Finish is clear anodized, painted or finished with a chemical conversion coating for field painting.

DE.2 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

REVEAL COLUMN RING

COLUMN DIAMETERS 18" TO 48"

DIM. A REVEAL WIDTH	DIM. B REVEAL DEPTH	NUMBER
1/2"	1/2"	WDM-50-50-625
1/2"	1/2"	DRWT-50-50
3/4"	3/4"	WRM-75-75-625
3/4"	3/4"	DRWT-75-75

DRYWALL (DRWT)



DRYWALL (DRWT)



ACOUSTICAL (WDM)



ACOUSTICAL (WDM)/ WRM)



COLUMN RING DETAIL



WALL ANGLE COLUMN RING

COLUMN DIAMETERS 18" TO 48"

TYPE	NUMBER
Acoustical	Wall Angle
Drywall	Wall Angle w/Taping Flange

DRYWALL



DRML -100

ACOUSTICAL/DRYWALL



M1WA 120

DRYWALL CROSS SECTION)



ACOUSTICAL/DRYWALL CROSS SECTION)



DF.1 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

"W" REVEAL MOLDING

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	DIM. C REVEAL DEPTH	NUMBER	
			NON-VENTED	VENTED
1/2"	1/2"	5/8"	WDM-50-50-625	WDM-50-V-50-625
1/2"	3/4"	1"	WDM-50-75	WDM-50-V-75
5/8"	3/4"	1"	WDM-625-75	WDM-625-V-75
3/4"	3/4"	5/8"	WRM-75-75-625	WRM-75-V-75-625



DF.2 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

DRYWALL / ACOUSTICAL REVEAL

REVEAL DEPTH	DIM. A	NUMBER
1/2"	1/2"	DRMAD-50-50
1/2"	3/4"	DRMAD-50-75



Drywall / Acoustical Reveal

DF.3 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

ACOUSTICAL CEILING TRIM

DIM. A	NUMBER
3/4"	DRAT-75
1"	DRAT-100



DF.4 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

ACOUSTICAL MOLDING

DIM. A STEP WIDTH	DIM. B STEP DEPTH	USAGE	NUMBER
1/2"	1/2"	1/2" Drywall	FDA-50
5/8"	5/8"	5/8" Drywall	FDA-625
3/4"	3/4"	3/4" Plaster	FDA-75



DF.5 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

"W" ACOUSTICAL REVEAL

MATERIAL POCKET	REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
7/8"	3/4"	WARM-875-75	WARM-875-V-75



DF.6 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

"F" ACOUSTICAL REVEAL

REVEAL DEPTH	REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
7/8"	3/4"	FARM-875-75	FARM-875-V-75



DF.7 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

"J" ACOUSTICAL TRIM

"J" DEPTH	NUMBER
7/8"	JAM-875





DG.1 PRODUCT DETAILS

SPECIAL SECTIONS

PRM MOLDING / PART NO. 1270



SPECIAL REVEAL MOLDING / PART NO. 1054



MODIFIED CHANNEL MOLDING / PART NO. 1858



SPECIAL REVEAL MOLDING / PART NO. "T" PIECE



SPECIAL "J" MOLDINGS / PART NO. 1360



DG.1 PRODUCT DETAILS

SPECIAL SECTIONS

SPECIAL "J" MOLDINGS / PART NO. 2054



SPECIAL "J" MOLDINGS / PART NO. 1262



DG.2 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

CONTEMPORARY REVEALS

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER
1/2"	1/2"	CDRM-50-50
1/2"	3/4"	CDRM-50-75
1/2"	1"	CDRM-50-100
5/8"	1/2"	CDRM-625-50
5/8"	5/8"	CDRM-625-625
5/8"	3/4"	CDRM-625-75
5/8"	1"	CDRM-625-100



DH.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

GLAZING TRACK

DIM A	NUMBER
3 1/2"	DMGT 3500
3 3/4"	DMGT 3750
4 5/8"	DMGT 4625
4 7/8"	DMGT 4875
7 1/4"	DMGT 7250

GLAZING TRACK



Glazing Track

GLASS GASKET SIZES

GLASS SIZE	GASKET NUMBER
FOR USE WITH 1/4" GLASS	RR 3657
FOR USE WITH 3/8" GLASS	RR 3654
FOR USE WITH 1/2" GLASS	RR 3730



DRYWALL CEILING TRACK (DRMAD-150-75)





GLAZING TRACK

DIM. A	NUMBER
3 1/2"	DMEC 3500
3 3/4"	DMEC 3750
4 5/8"	DMEC 4625
4 7/8"	DMEC 4875

DRYWALL MOLDING END CLOSURE (DMEC)



DMEC

ACOUSTICAL CEILING TRACK (ARM-150-75)





DRYWALL/ACOUSTICAL CEILING TRACK DRMAD-150-75)





DI.1 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

INTEGRATED FUNCTION REVEAL

INTEGRATED FUNCTIONAL REVEAL RAIL (IFRREVEAL)





USAGE

Fry Reglet Integrated Functional Reveal Rail creates a Horizontal reveal designed to accept a chartrail insert and hook insert. Provides an aesthetic reveal that is fully integrated into dry wall.



INTEGRATED FUNCTION REVEAL

2" AND 3" CHARTRAIL INSERT (IFRCHARTRAIL) (IFR3CHARTRAIL)





USAGE

Fry Reglet 2" and 3" Chartrail Insert to be inserted into the Integrated Functional Reveal Rail. Chartrail can be used to hold markers or as a stand for presentations or artwork.

GUIDE SPECIFICATION

Where indicated on drawings, Fry Reglet Chartrail Insert shall be installed. Aluminum shall be extruded alloy 6063 T5, with chemical conversion coating, clear anodized or other specified finish. Refer to finish section.

HOOK INSERT (IFRHOOKINSERT)

*(Hook insert) sold separately.
Note: Maximum capacity per hook insert is 75 pounds.
Not to exceed 4 clips per 10ft. peice





USAGE

Fry Reglet Hook Insert is designed to be inserted into the Integrated Functional Reveal Rail. Hooks can be placed anywhere on the reveal as needed, and repositioned for different sized objects like artwork, photography or presentations.

GUIDE SPECIFICATION

Where indicated on drawings, Fry Reglet Hook Insert shall be installed. Aluminum shall be extruded alloy 6063 T5. Standard finish clear anodized.

DJ.1 INSTALLATION

INSTALLATION GUIDE

TAPEABLE FLANGE SHAPES:

1. The moldings are installed after the gypsum board is installed. The installer can either provide space for the moldings at the time of installation or cut the board with a router.
2. The framer should provide backing so moldings may be attached with #6 drywall screws 16" o.c. for horizontal applications.
3. Prior to taping, the attachment flanges should be cleaned using a non-abrasive cleaner and soft rag. When veneer plaster is specified, the flanges must be treated with a bonding agent.
4. Make sure the tape does not overlap the edge of the reveal and an 8" wide trowel is used to apply the final skim coat.
5. Fiberglass, self-adhesive drywall tape will cut taping time and help to avoid possible cracking.

NON-TAPEABLE FLANGE SHAPES:

1. These types are installed prior to drywall installation and generally do not require taping or spackling.

ADDING SNAP-INS

1. When the reveal molding is used with the Snap-In, use the base molding with 1/2" ground when installing 1/2" drywall, and base molding with 5/8" ground when installing 5/8" drywall. (See "Right Way")
2. Make sure base is supported to ensure that the base does not become deformed when applying Snap-In.
3. NEVER use 1/2" base with 5/8" drywall when adding Snap-In. (See "Wrong Way")

RIGHT WAY



CORRECT INSTALLATION:
MOLDING INSTALLED FLUSH TO FRAMING

WRONG WAY



INCORRECT INSTALLATION:
MOLDING NOT INSTALLED FLUSH TO FRAMING

DJ.2 FACTORY FABRICATED INTERSECTIONS

INSTALLATION GUIDE

Factory fabricated intersections are available to connect horizontal and vertical joints of moldings of the same or different types. Intersections are available in “T”, “L”, and “+” shapes. The mitered joints are welded and the 6” legs are measured from the center point of the reveal. Corner pieces can be manufactured for both inside and outside conditions. Custom leg lengths are available.





DJ.3

INSTALLATION GUIDE

END CAPS

End Caps are not available for all products; please consult a customer service representative.



PCS END CAP WITHOUT FLANGE



DRM END CAP WITHOUT FLANGE



DRM END CAP WITH TAPING FLANGE



DRMB WITH END CAP

CUTTING + FIELD PAINTING

1. Materials can be cut with a chop saw, using a 96 tooth blade for non-ferrous metal.
2. Use a lubricant (WD-40 or grease stick) on the blade prior to cutting. Do not use an abrasive cut-off wheel.
3. Be sure to clean lubricant off trim.

If field painting of clear anodized moldings is the only alternative, the following steps must be taken to improve the bonding of the paint to the metal surface:

- Clean and treat material with an acid etch solution e.g. mild concentration of muriatic acid, rinse thoroughly and dry.
- Use a primer recommended by the manufacturer of the paint to be used.
- Apply coating following manufacturer's specifications.

However, Fry Reglet cannot accept responsibility for performance of field applied coatings over anodized finishes.

DJ.4 VENTILATION

VENTING INFORMATION



Example of vented profile with five rows of slots shown. Venting is available in one row of slots up to five rows. Specify number of rows required on your order.

USAGE

Moldings requiring venting are provided with vents for air movement. In size charts they are identified with a "V" in the center of the product number.

GUIDE SPECIFICATION

All vent slots are 1/8" wide by 1" long, spaced 11/2" on center lengthwise. Multiple rows are spaced laterally 1/2" on center. Each row of vent slots lengthwise provides approximately one square inch of vented area per lineal foot.

VENTILATION INFORMATION

REVEAL WIDTH	VENT SLOT	VENT AREA PER LINEAL FOOT APPROX.	PERCENT OF AREA VENTED APPROX.
1/2"	1	1 sq. inch	15.0%
3/4"	1	1 sq. inch	12.5%
7/8"	1	1 sq. inch	9.5%
1"	1	1 sq. inch	9.4%
1 1/8"	1	1 sq. inch	8.3%
1 1/2"	2	2 sq. inch	12.5%
2"	3	3 sq. inch	14.1%
2 1/2"	3	3 sq. inch	11.3%
3"	5	5 sq. inch	14.3%
4"	5	5 sq. inch	10.4%
6"	8	8 sq. inch	12.5%

CONTENTS

P Plaster + E.I.F.S Moldings

PA REVEALS AND CHANNEL SCREED /CONTROL JOINTS

- **PA.1** Channel Screed/Control Joint
- **PA.2** ¼"Channel Screed/Control Joint
- **PA.3** "V" Reveal Molding/Control Joint
- **PA.4** "F" Reveal Molding
- **PA.5** "T" Reveal Molding
- **PA.6** Plaster Key Reveal Molding
- **PA.7** Reveal Molding

PB COLUMN COLLARS

- **PB.1** Column Collar
- **PB.2** Column Collar

PC DRIP SCREEDS

- **PC.1** 7/8" Variable Fascia Drip Screed
- **PC.2** 7/8" Fascia Drip Screed
- **PC.3** 3/4" Fascia Drip Screed
- **PC.4** 5/8" Fascia Drip Screed
- **PC.5** 3/8" Fascia Drip Screed
- **PC.6** Soffit Molding
- **PC.7** "F" Drip Cap
- **PC.8** Foundation Weep Screed

PD PLASTER/STUCCO EXPANSION SCREED

- **PD.1** 2-Piece Plaster Expansion Screed

PE SOFFIT VENTS

- **PE.1** 7/8" Soffit Vent
- **PE.2** 3/4" Soffit Vent
- **PE.3** 5/8" Soffit Vent
- **PE.4** 7/8" Variable Soffit Vent
- **PE.5** Ceiling Soffit Vent
- **PE.6** Perimeter Soffit Molding
- **PE.7** Soffit Vent E.I.F.S.

PF TRIMS

- **PF.1** Fascia Corner Molding
- **PF.2** "J" Molding

PG CORNERS

- **PG.1** "X" Corner Molding
- **PG.2** Corner Key

PH E.I.F.S. MATERIALS

- **PH.1** E.I.F.S. Channel Screed
- **PH.2** E.I.F.S. Soffit Vent
- **PH.3** Clean Finish E.I.F.S. Soffit Vent
- **PH.4** E.I.F.S. Soffit Vent Direct Applied)
- **PH.5** E.I.F.S. Soffit Vent
- **PH.6** Soffit Vented E.I.F.S.

PI VENEER PLASTER

- **PI.1** Veneer Plaster Reveal
- **PI.2** Veneer Plaster "F" Reveal
- **PI.3** Veneer Plaster "Z" Reveal
- **PI.4** Contemporary Reveal

PJ INSTALLATION

- **PJ.1** Ventilation Information
- **PJ.2** Lathing - Vertical Installation
- **PJ.3** Lathing - Horizontal Installation
- **PJ.4** 2 Piece Plaster Expansion Screed
- **PJ.5** Factory Fabricated Intersections
- **PJ.6** Factory Fabricated Intersections
- **PJ.7** Factory Fabricated Intersections
- **PJ.8** Factory Fabricated Intersections
- **PJ.9** Factory Fabricated Intersections
- **PJ.10** Curved Moldings

PK FINISHES

- **PK.1** Finishes
- **PK.2** Finishes
- **PK.3** Finishes

P Plaster + E.I.F.S Moldings

GUIDE SPECIFICATION

Where indicated on drawings, Fry Reglet reveals and moldings, as manufactured by Fry Reglet Corporation, shall be installed. Fry Reglet aluminum reveals and moldings shall be extruded alloy 6063 T5, with chemical conversion coating, primed finish, clear anodized or other specified finish. Refer to finish section.

PA.1
CHANNEL SCREED /CONTROL JOINT

PA.2
1/4" CHANNEL SCREED /CONTROL JOINT



PA.3
"V" REVEAL MOLDING /CONTROL JOINT



PA.4
"F" REVEAL MOLDING

PA.5
"T" REVEAL MOLDING



PA.6
PLASTER KEY REVEAL MOLDING

PA.7
REVEAL MOLDING

PB.1
COLUMN COLLAR

PB.2
COLUMN COLLAR

PC.1
DRIP SCREED

PC.2
STUCCO DRIP SCREED



PC.3
3/4" FASCIA DRIP SCREED



PC.4
5/8" FASCIA DRIP SCREED



PC.5
3/8" FASCIA DRIP SCREED

PC.6
SOFFIT MOLDING



PC.7
"F" DRIP CAP

PC.8
FOUNDATION WEEP SCREED

PD.1
2-PIECE PLASTER EXPANSION SCREED

PE.1
7/8" SOFFIT VENT



PE.2
3/4" SOFFIT VENT



SHAPE FINDER INDEX

P Plaster + E.I.F.S Moldings

PE.3	PE.4	PE.5	PE.6	PF.1
5/8" SOFFIT VENT	7/8" VARIABLE SOFFIT VENT	CEILING SOFFIT VENT	PERIMETER SOFFIT MOLDING	FASCIA CORNER MOLDING
				

PF.2	PG.1	PG.2	PH.1	PH.2
"J" MOLDING	INSIDE / OUTSIDE "X" CORNER MOLDING	CORNER KEY	E.I.F.S. CHANNEL SCREED	E.I.F.S. SOFFIT VENT
				

PH.3	PH.4	PH.5	PH.6	PH.7
CLEANFINISH E.I.F.S. SOFFIT VENT	E.I.F.S. SOFFIT VENT DIRECT APPLIED)	E.I.F.S. SOFFIT VENT	E.I.F.S. DRIP SCREED	SOFFIT VENTED E.I.F.S.
				

PI.1	PI.2	PI.3	PI.4
VENEER PLASTER REVEAL MOLDING	VENEER PLASTER "F" REVEAL MOLDING	VENEER PLASTER "Z" REVEAL MOLDING	CONTEMPORARY REVEAL MOLDING
			

CHANNEL SCREED /CONTROL JOINT





DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
1/4"*	3/4"	PCS-25-75	PCS-25-V-75
1/4"*	1 1/2"	PCS-25-150	PCS-25-V-150
3/8"*	1/2"	PCS-375-50	PCS-375-V-50
3/8"*	3/4"	PCS-375-75	PCS-375-V-75
3/8"*	1"	PCS-375-100	PCS-375-V-100
3/8"*	1 1/2"	PCS-375-150	PCS-375-V-150
3/8"	3"	PCS-375-300	PCS-375-V-300
1/2"	1/2"	DCS-50-50	DCS-50-V-50
1/2"	3/4"	DCS-50-75	DCS-50-V-75
1/2"	1"	DCS-50-100	DCS-50-V-100
1/2"	1 1/2"	DCS-50-150	DCS-50-V-150
1/2"	2"	DCS-50-200	DCS-50-V-200
1/2"	3"	DCS-50-300	DCS-50-V-300
1/2"	4"	DCS-50-400	DCS-50-V-400
5/8"	1/2"	DCS-625-50	DCS-625-V-50
5/8"	3/4"	DCS-625-75	DCS-625-V-75
5/8"	1"	DCS-625-100	DCS-625-V-100
5/8"	1 1/2"	DCS-625-150	DCS-625-V-150

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
5/8"	2"	DCS-625-200	DCS-625-V-200
5/8"	2 1/2"	DCS-625-250	DCS-625-V-250
5/8"	3"	DCS-625-300	DCS-625-V-300
5/8"	4"	DCS-625-400	DCS-625-V-400
5/8"	6"	DCS-625-600	DCS-625-V-600
3/4"	1/2"	PCS-75-50	PCS-75-V-50
3/4"	3/4"	PCS-75-75	PCS-75-V-75
3/4"	1"	PCS-75-100	PCS-75-V-100
3/4"	1 1/2"	PCS-75-150	PCS-75-V-150
3/4"	2"	PCS-75-200	PCS-75-V-200
3/4"	2 1/2"	PCS-75-250	PCS-75-V-250
3/4"	3"	PCS-75-300	PCS-75-V-300
3/4"	4"	PCS-75-400	PCS-75-V-400
3/4"	6"	PCS-75-600	PCS-75-V-600
1"	3/4"	PCS-100-75	PCS-100-V-75
1"	1"	PCS-100-100	PCS-100-V-100
1"	3"	PCS-100-300	PCS-100-V-300
1 1/2"	1 1/2"	PCS-150-150	PCS-150-V-150

*For one-coat stucco systems
Weep holes available upon request

PA.2 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

1/4" CHANNEL SCREED /CONTROL JOINT

REVEAL WIDTH + DEPTH	NUMBER
1/4"	PCS-75-25/25





"V" REVEAL MOLING /CONTROL JOINT

REVEAL DEPTH	REVEAL WIDTH	NUMBER
3/4"	1 1/2"	PCSV-75
5/16"	3/4"	PCSV-75-Short









PA.4 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

"F" REVEAL MOLDING

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
3/8"	1/2"	FPM-375-50	FPM-375-V-50
1/2"	3/4"	FDM-50-75	FDM-50-V-75
5/8"	1/2"	FDM-625-50	FDM-625-V-50
5/8"	3/4"	FDM-625-75	FDM-625-V-75
5/8"	1"	FDM-625-100	FDM-625-V-100
5/8"	1 1/2"	FDM-625-150	FDM-625-V-150
5/8"	2 1/2"	FDM-625-250	FDM-625-V-250
5/8"	3"	FDM-625-300	FDM-625-V-300
3/4"	1/2"	FPM-75-50	FPM-75-V-50
3/4"	3/4"	FPM-75-75	FPM-75-V-75
3/4"	1"	FPM-75-100	FPM-75-V-100
3/4"	1 1/2"	FPM-75-150	FPM-75-V-150
3/4"	2"	FPM-75-200	FPM-75-V-200
3/4"	3"	FPM-75-300	FPM-75-V-300

Weep holes available upon request



PA.5 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

"T" REVEAL MOLDING

PLASTER THICKNESS	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
3/4"	3/4"	TRM-75-75	TRM-75-V-75
3/4"	1 1/8"	TRM-75-1125	TRM-75-V-1125
3/4"	1 1/2"	TRM-75-150	TRM-75-V-150



PA.6 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

PLASTER KEY REVEAL MOLDING

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
3/4"	7/8"	PRZ-75-75	PRZ-75-V-75
1"	3/4"	PRZ-75-100	PRZ-75-V-100



PA.7 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

REVEAL MOLDING

PLASTER THICKNESS	DIM. B REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
3/4"	3/4"	PRM-75-75	PRM-75-V-75

For use with columns, curved sizes available to fit columns above 18" in diameter.



PB.1 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

COLUMN COLLAR

DRYWALL



ACOUSTICAL/DRYWALL



PLASTER



USAGE

Fry Reglet Column Collar provides a functional, attractive trim creating a reveal at column/ceiling joint. PVC spacer insures an attractive appearance and no light leaks. Fabricated to fit specific column sizes. Tightens in place with a turnbuckle and stainless steel metal band. Available with white or dark bronze PVC spacer. Finish is clear anodized, painted or finished with a chemical conversion coating for field painting.

PB.2 INSTALLATION DETAIL / Cross Section

COLUMN COLLAR

DRYWALL



PLASTER



ACOUSTICAL/DRYWALL



SIZES

Column covers are manufactured to fit specific columns from 10" to 48" in diameter.

COMPONENTS

ADJUSTABLE BAND



ALUMINUM MOLDING







Three simple components secured by an adjustable band.

USAGE

Patented Fry Reglet Column Collar provides a functional, attractive trim creating a reveal at column/ceiling joint. PVC spacer insures an attractive appearance and no light leaks. Fabricated to fit specific column sizes. Tightens in place with a turnbuckle and stainless steel metal band. Available with white or dark bronze PVC spacer. Finish is clear anodized, painted or finished with a chemical conversion coating for field painting.

PC.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

7/8" VARIABLE FASCIA DRIP SCREED

NUMBER	
NON-VENTED	**VENTED**
DS-875-875	DS-875-V-875





7/8" FASCIA DRIP SCREED

DIM. A REVEAL WIDTH	NUMBER	
	NON-VENTED	VENTED
1 1/2"	DS-875-150	DS-875-V-150
2"	DS-875-200	DS-875-V-200
3"	DS-875-300	DS-875-V-300



DS-875-150



DS-875-200
DS-875-300



PC.3 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

3/4" FASCIA DRIP SCREED

STUCCO THICKNESS	DIM. A REVEAL WIDTH	NUMBER	
		NON-VENTED	VENTED
3/4"	3/4"	DS-75-75	DS-75-V-75
3/4"	2"	DS-75-200	DS-75-V-200
3/4"	3"	DS-75-300	DS-75-V-300

DS-75-75



DS-75-75



DS-75-200/300 (NOT TO SCALE)



DS-75-200/300



PC.4 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

5/8" DRIP SCREED

REVEAL WIDTH	NUMBER	
	NON-VENTED	VENTED
3"	DS-875-5/8-300	DS-875-5/8-V-300



PC.5 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

3/8" FASCIA DRIP SCREED

REVEAL WIDTH	NUMBER	
	NON-VENTED	VENTED
3/4"	DS-375-875	DS-375-V-875



PC.6 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

SOFFIT MOLDING

DIM. B THICKNESS	DIM. A REVEAL WIDTH	DIM. C LEG WIDTH	NUMBER	
			NON-VENTED	VENTED
1/2"	3"	1/2"	WPM-50-300	WPM-50-V-300
3/4"	2"	3/16"	1680	1680-V
3/4"	3"	3/16"	WPM-75-300	WPM-75-V-300
3/4"	4"	3/16"	WPM-75-400	WPM-75-V-400



PC.7 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

"F" DRIP CAP

STUCCO DEPTH	REVEAL WIDTH	NUMBER
3/4"	3/4"	2221

Weep holes available upon request



PC.8 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

FOUNDATION WEEP SCREED

SCREED LENGTH	FLANGE DEPTH	NUMBER
3 3/8"	3/4"	FWS-75A (Aluminum)
3 3/8"	3/4"	FWS-75 (Vinyl)



PD.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

2-PIECE PLASTER EXPANSION SCREED

DIM. A	DIM. B REVEAL WIDTH	NUMBER
1/2"	3/4"	DCS-50-75 2-PC
1/2"	1 1/2"	DCS-50-150 2-PC
3/4"	1/4"	PCS-75-25 2-PC
3/4"	1/2"	PCS-75-50 2-PC
3/4"	3/4"	PCS-75-75 2-PC
3/4"	1"	PCS-75-100 2-PC
3/4"	1 1/2"	PCS-75-150 2-PC
3/4"	2"	PCS-75-200 2-PC



PE.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

7/8" SOFFIT VENT

DIM. A REVEAL WIDTH	NUMBER
1 1/2"	DS-875-V-150
2"	DS-875-V-200
3"	DS-875-V-300

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.

DS-875-150



PE.2 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

3/4" SOFFIT VENT

DIM. A REVEAL WIDTH	NUMBER
3/4"	DS-75-V-75
2"	DS-75-V-200
3"	DS-75-V-300

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.



PE.3 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

5/8" SOFFIT VENT

SOFFIT SUPPORT FLANGE	REVEAL WIDTH	NUMBER
5/8"	3"	DS-875-5/8-V-300

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.



PE.4 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

7/8" VARIABLE SOFFIT VENT

DIM. A REVEAL WIDTH	NUMBER
7/8"	DS-375-V-875

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.



PE.5 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

CEILING SOFFIT VENT





DIM. A PLASTER DEPTH	DIM. B REVEAL WIDTH	NUMBER
1/2"	1/2"	DCS-50-V-50
1/2"	3/4"	DCS-50-V-75
1/2"	1"	DCS-50-V-100
1/2"	1 1/2"	DCS-50-V-150
1/2"	2"	DCS-50-V-200
1/2"	3"	DCS-50-V-300
1/2"	4"	DCS-50-V-400
5/8"	1/2"	DCS-625-V-50
5/8"	3/4"	DCS-625-V-75
5/8"	1"	DCS-625-V-100
5/8"	1 1/2"	DCS-625-V-150
5/8"	2"	DCS-625-V-200
5/8"	2 1/2"	DCS-625-V-250
5/8"	3"	DCS-625-V-300
5/8"	4"	DCS-625-V-400
5/8"	6"	DCS-625-V-600
1/4"	3/4"	PCS-25-V-75

DIM. A PLASTER DEPTH	DIM. B REVEAL WIDTH	NUMBER
3/8"	1/2"	PCS-375-V-50
3/8"	3/4"	PCS-375-V-75
3/8"	1"	PCS-375-V-100
3/8"	1 1/2"	PCS-375-V-150
3/8"	3"	PCS-375-V-300
3/4"	1/2"	PCS-75-V-50
3/4"	3/4"	PCS-75-V-75
3/4"	1"	PCS-75-V-100
3/4"	1 1/2"	PCS-75-V-150
3/4"	2"	PCS-75-V-200
3/4"	2 1/2"	PCS-75-V-250
3/4"	3"	PCS-75-V-300
3/4"	4"	PCS-75-V-400
3/4"	6"	PCS-75-V-600
1"	3/4"	PCS-100-V-75
1"	1"	PCS-100-V-100
1"	3"	PCS-100-V-300
1 1/2"	1 1/2"	PCS-150-V-150

*See page PJ-1 for data on number of vents and amount of vented areas/sq. ft.

PE.6 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

PERIMETER SOFFIT MOLDING

DIM B. STUCCO DEPTH	DIM. A REVEAL WIDTH	DIM. C LEG WIDTH	NUMBER
1/2"	3"	1/2"	WPM-50-V-300
3/4"	2"	3/16"	1680-V
3/4"	3"	3/16"	WPM-75-V-300
3/4"	4"	3/16"	WPM-75-V-400

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.



PE.7 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

SOFFIT VENT E.I.F.S.

VENT PATTERN*	NUMBER
5 Rows	VFS-600 Epoxy Gray
8 Rows	VFS-600 Epoxy Gray

*Specify vent pattern when ordering.
Vent Slots 1/8" wide by 1" long spaced 1 1/2" on center lengthwise.

8 ROWS



5 ROWS



PF.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

FASCIA CORNER MOLDING

DIM. A REVEAL WIDTH	DIM. A	DIM. B	NUMBER	APPLICATION
1 5/8"	5/8"	1/2"	FCM-50	DRYWALL
1 5/8"	3/4"	5/8"	FCM-75	PLASTER



Fascia Corner Molding

PF.2 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

"J" MOLDING

DIM. A	DIM. B	DIM. C	NUMBER
1/2"	3/16"	1 1/8"	JDM-50
5/8"	3/16"	1 1/8"	JDM-625
3/4"	3/16"	1 1/8"	JPM-75
3/4"	3/16"	3"	JPM-75-300
1"	3/16"	1 1/8"	JPM-100

Weep holes available upon request



"J" Molding

"X" CORNER MOLDING

XCM

DIM. A REVEAL WIDTH	DIM. B REVEAL DEPTH	NUMBER
3/4"	7/8"	XCM-75-75
1/2"	7/8"	XDM-50-50
5/8"	7/8"	XDM-625-625
3/4"	1 1/2"	XCM-75-75-150

PXM

DIM. A REVEAL WIDTH	NUMBER
7/8"	PXM-75-75

PIXM

REVEAL WIDTH	NUMBER
3/4"	PIXM-75-75

OUTSIDE CORNER
XCM-75-75
XDM-50-50
XDM-625-625
XCM-75-75-150



OUTSIDE CORNER
PXM-75-75



Thickness .055"

INSIDE CORNER
PIXM-75-75



CORNER KEY

NUMBER	DIM.
PCM-75-75	3/4"
PCM-75-75-150	1 1/2"



PH.1 PRODUCT DETAIL

INSTALLATION DETAILS / Cross Section

E.I.F.S. CHANNEL SCREED

DIM. A REVEAL WIDTH	NUMBER	
	NON-VENTED	VENTED
3/4"	PCS-25-75	PCS-25-V-75
1 1/2"	PCS-25-150	PCS-25-V-150



PH.2 PRODUCT DETAIL

INSTALLATION DETAILS / Cross Section

E.I.F.S. SOFFIT VENT

DIM. A	NUMBER
1/2"	PCS-75-V-50
3/4"	PCS-75-V-75
1"	PCS-75-V-100
1 1/2"	PCS-75-V-150
2"	PCS-75-V-200
2 1/2"	PCS-75-V-250
3"	PCS-75-V-300
4"	PCS-75-V-400
6"	PCS-75-V-600

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.



PH.3 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

CLEANFINISH E.I.F.S. SOFFIT VENT

DIM. A	DIM. B	NUMBER	UNVENTED
1/2"	2"	SV-50-V-200/EIFS	SV-50-200/EIFS
1/2"	3"	SV-50-V-300/EIFS	SV-50-300/EIFS
1/2"	4"	SV-50-V-400/EIFS	SV-50-400/EIFS
3/4"	3"	SV-75-V-300/EIFS	SV-75-300/EIFS

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.



PH.4 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

E.I.F.S. SOFFIT VENT DIRECT APPLIED

DIM. A	DIM. B REVEAL WIDTH	NUMBER
1/2"	1/2"	DRM-50-V-50
1/2"	5/8"	DRM-50-V-625
1/2"	3/4"	DRM-50-V-75
1/2"	1"	DRM-50-V-100
1/2"	1 1/2"	DRM-50-V-150
1/2"	2"	DRM-50-V-200
1/2"	2 1/2"	DRM-50-V-250
1/2"	3"	DRM-50-V-300
1/2"	4"	DRM-50-V-400

DIM. A	DIM. B REVEAL WIDTH	NUMBER
5/8"	1/2"	DRM-625-V-50
5/8"	5/8"	DRM-625-V-625
5/8"	3/4"	DRM-625-V-75
5/8"	1"	DRM-625-V-100
5/8"	1 1/4"	DRM-625-V-125
5/8"	1 1/2"	DRM-625-V-150
5/8"	2"	DRM-625-V-200
5/8"	2 1/2"	DRM-625-V-250
5/8"	3"	DRM-625-V-300
5/8"	4"	DRM-625-V-400
5/8"	6"	DRM-625-V-600

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.



*Denglass Gold, Durock, or other approved DEF substrate.
*Refer to EIFS manufacturer for installation requirements

PH.5 PRODUCT DETAIL

E.I.F.S. SOFFIT VENT

VENT PATTERN*	NUMBER
5 Rows	VFS-600 Epoxy Gray
8 Rows	VFS-600 Epoxy Gray

*Specify vent pattern when ordering. Vent Slots $^1/_8$" wide by 1" long spaced $1^1/_2$" on center lengthwise.



INSTALLATION DETAILS / Cross Section

8 ROWS



5 ROWS



PH.6 PRODUCT DETAIL

E.I.F.S. DRIP SCREED

DIM. A REVEAL WIDTH	NUMBER	
	NON-VENTED	VENTED
$^3/_4$"	DS-75-75	DS-75-V-75
2"	DS-75-200	DS-75-V-200
3"	DS-75-300	DS-75-V-300

*See page PJ-1 for data on number of vents and amount of vented area/sq. ft.

INSTALLATION DETAILS / Cross Section



VENEER PLASTER REVEALS
SLEEK + SLIM.

Fry Reglet offers a selection of aluminum reveals and molding specifically designed for use with veneer plaster.







PI.1 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

VENEER PLASTER REVEAL MOLDING

DIM. A	DIM. B	NUMBER
3/8"	3/8"	VPR-375-375
1/2"	1/2"	VPR-50-50
1/2"	3/4"	VPR-50-75
1/2"	1 1/2"	VPR-50-150
5/8"	3/8"	VPR-625-375
5/8"	1/2"	VPR-625-50
5/8"	5/8"	VPR-625-625
5/8"	3/4"	VPR-625-75



PI.2 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

VENEER PLASTER "F" REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER
3/8"	3/8"	VPRF-375-375
1/2"	1/2"	VPRF-50-50
1/2"	3/4"	VPRF-50-75
5/8"	3/8"	VPRF-625-375
5/8"	1/2"	VPRF-625-50
5/8"	5/8"	VPRF-625-625
5/8"	3/4"	VPRF-625-75



PI.3 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

VENEER PLASTER "Z" REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER
3/8"	3/8"	VPRZ-375-375
1/2"	1/2"	VPRZ-50-50
1/2"	3/4"	VPRZ-50-75
5/8"	3/8"	VPRZ-625-375
5/8"	1/2"	VPRZ-625-50
5/8"	5/8"	VPRZ-625-625
5/8"	3/4"	VPRZ-625-75



PI.4 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

CONTEMPORARY REVEAL

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH	NUMBER
1/2"	1/2"	CVPR-50-50
1/2"	5/8"	CVPR-50-625
1/2"	3/4"	CVPR-50-75
1/2"	1"	CVPR-50-100
5/8"	1/2"	CVPR-625-50
5/8"	5/8"	CVPR-625-625
5/8"	3/4"	CVPR-625-75
5/8"	1"	CVPR-625-100



U.S. Patent No. 452,016

PJ.1 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

VENTILATION INFORMATION

REVEAL WIDTH	VENT SLOT	VENT AREA PER LINEAL FOOT APPROX.	PERCENT OF AREA VENTED APPROX.
1/2"	1	1 sq. inch	15.0%
3/4"	1	1 sq. inch	12.5%
7/8"	1	1 sq. inch	9.5%
1"	1	1 sq. inch	9.4%
1 1/8"	1	1 sq. inch	8.3%
1 1/2"	2	2 sq. inch	12.5%
2"	3	3 sq. inch	14.1%
2 1/2"	3	3 sq. inch	11.3%
3"	5	5 sq. inch	14.3%
4"	5	5 sq. inch	10.4%
6"	8	8 sq. inch	12.5%



Example of vented profile with five rows of slots shown. Venting is available in one row of slots up to five rows. Specify number of rows required on your order.

PJ.2 INSTALLATION

LATHING VERTICAL INSTALLATION

LATHING - VERTICAL INSTALLATION

1. Place building paper behind all moldings and shiplap a minimum of 6".
2. Secure moldings on 7" centers using fasteners as appropriate to substrate to meet ASTM C1063.
3. Install wire lath over installation flange of moldings.
4. Use vinyl or cloth tape specifically manufactured for masking anodized aluminum trim prior to plastering. For painted surfaces, use plastic tape.



LATHING - HORIZONTAL INSTALLATION

1. Place building paper behind all moldings and shiplap a minimum of 6".
2. Secure moldings on 16" centers using fasteners as appropriate to substrate.
3. Place building paper over upper flange of reveal, extending upward and under the above building paper overlap.
4. Place wire lath over upper installation flange on horizontal installation.
5. Install wire lath over bottom installation flange of moldings.
6. Use vinyl or cloth tape specifically manufactured for masking aluminum trim prior to plastering. For painted surfaces, use plastic tape.

INSTALLATION OF MOLDINGS AFTER BUILDING PAPER AND WIRE LATH HAVE BEEN INSTALLED

Make sure that the 7/8" installation flanges are covered with wire lath. This will prevent cracking.

Note: Uniform Building Code requires two layers of grade "D" paper when applied over wood base sheathing.



PJ.4 INSTALLATION

INSTALLATION 2-PIECE PLASTER EXPANSION JOINT

INSTALLATION - 2-PIECE PLASTER EXPANSION JOINT

1. Place building paper behind all moldings and shiplap a minimum of 6".
2. Prior to attachment, place sealant in the movement groove along the back of the molding. **NOTE:** If installation is horizontal, place movement flange on top and lap additional building paper over top flange.
3. Leave alignment clips in place while fastening moldings to framing or studs.
4. Secure moldings on 16" centers using fasteners as appropriate to substrate.
5. Place building paper and wire lath over upper movement installation flange on horizontal installation, and shiplap a minimum of 6". (See Horizontal Installation)
6. Install wire lath over bottom installation flange of moldings.
7. Use vinyl or cloth tape specifically manufactured for masking anodized aluminum trim prior to plastering. For painted surfaces, use plastic tape. **NOTE:** Qualifies for use as an expansion joint for stucco and plaster applications when installed in accordance with ASTM C1063.



SEALANT + CONNECTOR CLIPS

1. The use of sealant at all butt joints and Fry Reglet Connector Clips is recommended.
2. Use Fry Reglet Connector Clips to align molding during installation.
3. Apply sealant as indicated.



PJ.5 FACTORY FABRICATED INTERSECTIONS

FACTORY FABRICATED INTERSECTIONS

Factory fabricated intersections and corner pieces of the same or different moldings are used to connect horizontal and vertical joints, or transitioning from plane to plane. The intersections are welded and sealed. Standard leg lengths are 6" from the center point of the reveal. Custom leg lengths are available.

"T" INTERSECTION



End Caps are not available for all products; please consult a customer service representative.



"+" INTERSECTION



PJ.6 FACTORY FABRICATED INTERSECTIONS

FACTORY FABRICATED INTERSECTIONS

FACTORY FABRICATED INTERSECTIONS

Presented as examples of ways Factory Fabricated Intersections can be used to speed installation and reduce costs.

PREFABRICATED AND PRE-ASSEMBLED JOINTS

Factory fabricated intersections are available from Fry Reglet to speed installation and reduce labor cost. Intersections are available in the configurations shown below as well as custom configurations and may be made up of the same or different shapes. The joints are welded.

NOTE: Water resistant tape is factory applied to the backs of all PCS and DCS factory fabricated intersections.

Intersections are furnished with 6" legs to join with straight sections of moldings.

Custom leg lengths are available.

PCS CHANNEL REVEAL "L" INTERSECTION



END CAP



DRMB WITH END CAP





End Caps are not available for all products; please consult a customer service representative.

FACTORY FABRICATED INTERSECTIONS

FACTORY FABRICATED INTERSECTIONS

Presented as examples of ways Factory Fabricated Intersections can be used to speed installation and reduce costs.

PCS CHANNEL REVEAL INSIDE CORNER



PCS CHANNEL REVEAL OUTSIDE CORNER



PCS CHANNEL REVEAL "+" INTERSECTION



PCS CHANNEL REVEAL "T" INTERSECTION



PJ.8 FACTORY FABRICATED INTERSECTIONS

FACTORY FABRICATED INTERSECTIONS

FACTORY FABRICATED INTERSECTIONS

Presented as examples of ways Factory Fabricated Intersections can be used to speed installation and reduce costs.

DRM/DRMZ INTERSECTION AT DOORJAMB



PCS/PCS 2-PC INTERSECTION



FPM/PCS WINDOW SILL REVEAL



XCM/PCS CORNER/INTERSECTION



FACTORY FABRICATED INTERSECTIONS

FACTORY FABRICATED INTERSECTIONS

Fry Reglet's expertise at curving moldings combined with factory fabrication of intersections at virtually any angle, permits the complete assembly of decorative elements ready for installation. Two examples are shown below. The first uses curved and straight sections of the same drywall part and the second combines three plaster parts for an intriguing effect. Designers may let their imaginations soar. All that is required is a sketch together with the parts to be used. Fry Reglet will design the decorative element, quote a complete price and furnish a complete assembly, ready to install.

EXAMPLE 1

A SINGLE MOLDING – FACTORY FABRICATED



PART USED: DRM-50-50 DRYWALL REVEAL MOLDING

DESCRIPTION

A straight and curved assembly of reveal moldings serves as the base of this intricate fabrication combining corners and intersections at various angles with straight and curved sections of moldings.

EXAMPLE 2

VARIOUS DISSIMILAR MOLDINGS – FACTORY FABRICATED



PARTS USED: PCS-75-75 PLASTER CHANNEL SCREED

PCS-75-150 PLASTER CHANNEL SCREED

PCS-75-200 PLASTER CHANNEL SCREED

DESCRIPTION

Fry Reglet Plaster Channel Screeds with three reveal widths (3/4", 11/2" and 2") are combined to produce this intricate pattern. The widest reveal frames the entire assembly while 11/2" width is curved into an attractive design element. The center pattern is assembled from the narrowest moldings.

PJ.10 CURVED MOLDINGS

CURVED MOLDINGS

With over 20 years experience curving aluminum moldings, Fry Reglet is the leader in this technology. Fry Reglet's curving process is precise and our aluminum moldings hold their shape from the factory to the job site. Whether conforming to conditions such as archways, columns and curved ceilings; or when using Fry Reglet moldings to create a pattern within the wall, Fry Reglet's curving capability can add surprisingly dramatic effects to any project.

CURVING FRY REGLET MOLDINGS

Fry Reglet is able to curve virtually any shape in our assortment of drywall and plaster moldings. The only limitation to this process is the size of the curve, measured in terms of the "radius". Radius is the geometric term given to the distance from the center of a circle to its outside edge. The shape of the molding, and the direction of the curve, determine the minimum curve that can be achieved. Contact your local distributor or Fry Reglet's Customer Service Department for price quotations, radius minimums for specific parts and radius order forms.

Fry Reglet's curving process yields 9 usable feet of material from each 10 foot part. Provision for this 10% spoilage should be made when ordering.





CURVED TERMINOLOGY

Measuring Radius

In measuring curves, careful attention should be given to the point on the molding to which the radius is measured. Radius detail sheet indicates Point of Measurement.

ORDERING CURVED MOLDINGS

To assist in ordering curved moldings, Fry Reglet requests specific detailed information. By following the simple steps below, you are assured of obtaining the exact radius desired.

Indicate Curve Desired

Contact Fry Reglet Customer Service to obtain radius order sheets.

Indicate Radius

Indicate the radius desired from measuring points on radius detail. In most cases the radius measurement should be field checked.

Indicate Molding + Finish Desired

Indicate number of molding and finish desired (i.e. DRM 50-150 clear anodized).

Indicate Quantity

Indicate total footage desired (add 10% for spoilage).

For additional specification and ordering information contact a customer service representative.

PK.1 DRYWALL / PLASTER MOLDING FINISHES

FINISHES

POWDER PAINT

Fry Reglet Powder paint, applied over chemical conversion coating and primer, provides durability and beauty for most interior and exterior applications. This finish is provided as the standard Fry Reglet paint finish.

This factory applied, baked-on finish is available at standard lead times in the colors shown and in custom colors to match swatches provided

SPECIFICATION

Powder Paint Shall Be As Follows:
All surfaces to receive a polyester powder coat will be pretreated in strict accordance with the powder coating manufacturer's specification.

Finish total dry film thickness should meet or exceed the dry film thickness of 30 microns/ 1.2 mils as specified in AAMA 2605 SEC 4.3. Color uniformity will meet or exceed the requirements of AAMA 2605 SEC 7.1

KYNAR® PREMIUM FINISH

The industry standard for over 25 years, Fry Reglet Kynar® coatings provide superior resistance to chalking and ultraviolet deterioration. Kynar® finishes are highly resistant to chemicals, salt spray and industrial pollutants. This premium finish is recommended for moldings to be used on exteriors in harsh environments or in coastal areas where salt air is common. Available in all standard Kynar colors and custom colors to match swatches provided.

Kynar® is a registered trademark of ALTOFINA.

SPECIFICATION

Kynar® Finish Shall Be As Follows:
Finish shall meet or exceed AAMA 2605 Specification "Voluntary Specification for High Performance Organic Coatings on Architectural Extrusion Panels." (Nominal dry film thickness shall be .30 mil for primer and 1.0 mil for finish coats).

Finish shall be 70% min. resin content full strength) polyvinylidene fluoride coating, applied over chemical conversion coating and primer. Coatings shall receive a bake cycle of 17 minutes at 450°F. Kynar® is available by special order only. Contact Fry Reglet for color information.

PK.2 DRYWALL / PLASTER MOLDING FINISHES

FINISHES

Tan | Medium Bronze | Dark Bronze | Cream

White | Black | Oyster | Haze

Adobe | Silver Satin | Silver Gray | Platinum

Gun Metal Gray

PK.3 DRYWALL / PLASTER MOLDING FINISHES

FINISHES

ANODIZED FINISHES

Anodizing is an electrochemical process in which the aluminum is immersed in an acid solution through which electric current is passed. Although a natural oxidation process commences when bare, unfinished aluminum is exposed to air, producing the oxide film artificially creates a film that is thicker, harder and more durable.

Other anodic coatings are available on special order to satisfy architectural requirements. Colors available are:

- Medium Bronze
- Light Bronze
- Dark Bronze
- Black

These integral colors are in conformance with the Aluminum Association designation 3AA-M112C22A32.

Also available on special order are other colors using various two-step processes in conformance with the Aluminum Association designation 3AA-12C22A34 for impregnated color. These specifications for color anodizing are for Class II architectural finishes with coating thicknesses up to 0.7 mils.

general note concerning anodized finishes: Due to the nature of the anodizing process, shade variations can be expected from one element to another. This inherent characteristic of the finish need be no problem if properly anticipated in the design.

SPECIFICATION

Clear Anodized Finish Shall Be As Follows:

STANDARD: Architectural 200R1 medium etch (AA-M32C10A21).

SPECIAL ORDER: Class II Architectural 204R1 medium etch .40 mils min. (AA-M12C22A31)

Thickness of anodic coating shall be tested in accordance with ASTM B-244-68 and sealed to pass the modified dye stain test (ASTM B136-77).

CHEMICAL CONVERSION COAT FINISHES

Chemical conversion coating is a multi-step cleaning and metal preparation process. It cleans the aluminum, and acts as a protective coating until primer and paint can be applied. When field painting is planned, chemical conversion coating should be specified.

SPECIFICATION

Chemical Conversion Coat Finish Shall Be As Follows: Treatment of aluminum moldings to conform with ASTM D 1730 Type B and MIL-C-5541A.

PRIME PAINTING

Fry Reglet Prime Paint is spray applied in the factory and baked-on so that it serves as an ideal base for finish painting in the field.

SPECIFICATION

Prime Paint Shall Be As Follows:

Factory sprayed and baked-on to serve as a base for field painting.

PRECISION TRIMS
PERFECTLY EXECUTED.

In collaboration with an industry leading fiber cement panel manufacturer, Fry Reglet designed a comprehensive trim system, specifically engineered for 5/16" fiber cement panels. This series of extruded aluminum trims provides a smooth, seamless, installation friendly system that is unparalleled in the fiber cement panel industry. Vertical and horizontal trims align perfectly and allow for panels to be installed according to the panel manufacturer's prescribed fastener schedule without causing panel breakage or bowing. All trims are available in primed, clear anodized or factory powder coat, custom color or perfectly matched to the fiber cement panel manufacturer's pre-finished color panels.

For more than 65 years, Fry Reglet has been the trusted source for superior metal fabrications and component systems. All of Fry Reglet's products embody precision engineering, expert manufacturing and inherent sustainability. At Fry Reglet, we pride ourselves on guaranteed quality, hands-on customer service that has solidified our reputation of excellence, unmatched by our competitors.

SHAPE FINDER INDEX

A Trims

TRIMS

A.1	F Molding	**A.23**	W Inside Corner Lap Trim
A.2	J-Channel	**A.24**	J Channel Lap Trim
A.3	Vertical H Mold	**A.25**	F Channel Lap Trim
A.4	Vertical Molding	**A.26**	Lap Wall Angle
A.5	Vertical Retainer	**A.27**	Soffit Vent
A.6	Vertical Insert	**A.28**	Double T 1/2”
A.7	Vertical Offset	**A.29**	Double T 1/4”
A.8	Vertical Lap Insert	**A.30**	T Piece
A.9	Base	**A.31**	Double OSC
A.10	Horizontal	**A.32**	Sleek OSC Lap
A.11	Horizontal Notch	**A.33**	Sleek OSC
A.12	Double Horizontal	**A.34**	Double Drip Cap
A.13	Drip Cap / Drip Cap 875	**A.35**	Lap/Panel Wall Angle
A.14	Inside Corner	**A.36**	Batten OSC
A.15	Integral Inside Corner	**A.37**	Artisan OSC
A.16	Inside Corner Transition	**A.38**	Rain Screen Vent Strip
A.17	Integral Inside Lap Corner	**A.39**	Artisan ISC
A.18	Outside Corner	**A.40**	J-Channel 1060
A.19	Bullnose Outside Corner	**A.41**	Vertical H Mold 1060
A.20	Outside Corner Transition	**A.42**	Integral Outside Corner 1060
A.21	Integral Outside Corner / Lap Corner	**A.43**	Outside Corner 1060
A.22	X Outside Corner Lap Trim		

AB

FINISHES

AB.1 Finishes

A Trims

USAGE

This chart is designed to help you locate a specific shape in the Fry Reglet Shape Finder. Find the shape you want. Detailed information can be found on the page number above the shape.

A.1	A.2	A.3	A.4	A.5
VERTICAL / HORIZONTAL F MOLDING	VERTICAL / HORIZONTAL J-CHANNEL	VERTICAL H MOLD	VERTICAL MOLDING	VERTICAL RETAINER

A.6	A.7	A.8	A.9	A.10
VERTICAL INSERT	VERTICAL OFFSET	VERTICAL LAP INSERT	BASE	HORIZONTAL
				

A.11	A.12	A.13	A.14	A.15
HORIZONTAL NOTCH	DOUBLE HORIZONTAL	DRIP CAP / DRIP CAP 875	INSIDE CORNER	INTEGRAL INSIDE CORNER

A.16	A.17	A.18	A.19	A.20
INSIDE CORNER TRANSITION	INTEGRAL INSIDE LAP CORNER	OUTSIDE CORNER	BULLNOSE OUTSIDE CORNER	OUTSIDE CORNER TRANSITION
				

A.21	A.22	A.23	A.24	A.25
INTEGRAL OUTSIDE CORNER / LAP CORNER	X OUTSIDE CORNER LAP TRIM	W INSIDE CORNER LAP TRIM	J CHANNEL LAP TRIM	F CHANNEL LAP TRIM
				

SHAPE FINDER INDEX

A Trims

A.26	A.27	A.28	A.29	A.30
LAP WALL ANGLE	SOFFIT VENT	DOUBLE T 1/2"	DOUBLE T 1/4"	T PIECE
				

A.31	A.32	A.33	A.34	A.35
DOUBLE OSC	SLEEK OSC LAP	SLEEK OSC	DOUBLE DRIP CAP	LAP/PANEL WALL ANGLE
				

A.36	A.37	A.38	A.39	A.40
BATTEN OSC	ARTISAN OSC	RAIN SCREEN VENT STRIP	ARTISAN ISC	J CHANNEL 1060
				

A.41	A.42	A.43
VERTICAL H MOLD 1060	INTEGRAL OUTSIDE CORNER 1060	OUTSIDE CORNER 1060
		

A.1 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

F MOLDING

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-F MOLD





A.2 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

J CHANNEL

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-J CHANNEL





J Channel

J Channel

A.3 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

VERTICAL H MOLDING

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-H VERT MOLD





A.4 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

VERTICAL MOLDING

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-VERTICAL





A.5 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

VERTICAL RETAINER

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-VERT RET





A.6 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

VERTICAL INSERT

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-VERT INSERT





A.7 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

VERTICAL OFFSET

REVEAL DEPTH	REVEAL DEPTH	NUMBER
NOM. 3/4"	NOM. 3/8"	FCP-VERT OFFSET





A.8 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

VERTICAL LAP INSERT

REVEAL DEPTH	NUMBER
NOM. 3/4"	FCP-VERT INS75





A.9 PRODUCT DETAIL | INSTALLATION DETAIL / Cross Section

BASE

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-BASE





A.10 PRODUCT DETAIL | INSTALLATION DETAIL / Cross Section

HORIZONTAL

REVEAL DEPTH	NUMBER
NOM. 1/2"	FCP-HOZ TRIM





A.11 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

HORIZONTAL NOTCHED

REVEAL DEPTH	NUMBER
NOM. 1/2"	FCP-HOZ NOTCH





A.12 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

DOUBLE HORIZONTAL

REVEAL DEPTH	NUMBER
NOM. 1/2"	FCP-DBLHOZ TRIM





A.13 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

DRIP CAP / DRIP CAP 875

DIM. A REVEAL DEPTH	DIM. B	DIM. C	NUMBER
7/8"	1 1/2"	1/2"	FCP-DRIP CAP 875
1 7/16"	1 3/4"	3/8"	FCP-DRIP CAP





A.14 PRODUCT DETAIL

INSTALLATION DETAIL / Cross Section

INSIDE CORNER

REVEAL DEPTH	NUMBER
1/2"	FCP-INSIDE CNR





A.15 PRODUCT DETAIL

INTEGRAL INSIDE CORNER

REVEAL DEPTH	NUMBER
3/8"	FCP-INTISCNR



INSTALLATION DETAIL / Cross Section



A.16 PRODUCT DETAIL

INSIDE CORNER TRANSITION

REVEAL DEPTH	NUMBER
3/8"	FCP-I/SCRNTR



INSTALLATION DETAIL / Cross Section



A.17 PRODUCT DETAIL

INTEGRAL INSIDE LAP CORNER

REVEAL DEPTH	NUMBER
3/4"	FCP-INTISCNR750



INSTALLATION DETAIL / Cross Section



A.18 PRODUCT DETAIL

OUTSIDE CORNER

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-OUTSIDE CNR



INSTALLATION DETAIL / Cross Section



A.19 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

BULLNOSE OUTSIDE CORNER

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-BULLNOSE





A.20 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

OUTSIDE CORNER TRANSITION

REVEAL DEPTH	REVEAL DEPTH	NUMBER
NOM. 3/8"	NOM. 3/4"	FCP-O/SCRNTR





A.21 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

INTEGRAL OUTSIDE CORNER

INTEGRAL OUTSIDE LAP CORNER

DIM A REVEAL DEPTH	DIM B	NUMBER
NOM. 3/4"	NOM. 2 3/8"	FCP-INTO/SCNR750
NOM. 3/8"	NOM. 1 3/4"	FCP-INT OSCNR





A.22 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

X OUTSIDE CORNER LAP TRIM

REVEAL DEPTH	NUMBER
NOM. 3/4"	FCP-PXM7575





A.23 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

W INSIDE CORNER LAP TRIM

REVEAL DEPTH	NUMBER
NOM. 3/4"	FCP-WRM-75-75





A.24 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

J CHANNEL LAP TRIM

J DEPTH	NUMBER
NOM. 3/4"	FCP-JAM-75





A.25 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

F CHANNEL LAP TRIM

REVEAL DEPTH	NUMBER
NOM. 3/4"	FCP-FARM-75-50





A.26 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

LAP WALL ANGLE

REVEAL DEPTH	NUMBER
NOM. 3/4"	FCP-WA75100





A.27 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

SOFFIT VENT

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-PCS375V300





A.28 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

DOUBLE T 1/2"

REVEAL DEPTH	NUMBER
NOM. 7/16"	FCP-VERTLP50





A.29 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

DOUBLE T 1/4"

REVEAL DEPTH	NUMBER
NOM. 7/16"	FCP-VERTLP25





A.30 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

T PIECE

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-T-PIECE





A.31 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

DOUBLE OSC

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-DBLOSC





A.32 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

SLEEK OSC LAP

REVEAL DEPTH	NUMBER
NOM. 13/16"	FCP-LPO/SCNRLAP





A.33 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

SLEEK OSC

REVEAL DEPTH	NUMBER
1 3/8"	FCP-LPO/SCNR





A.34 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

DOUBLE DRIP CAP

DIM. A REVEAL DEPTH	DIM. B	NUMBER
1 1/2"	1 5/16"	FCP-DRIPCAPDBL





A.35 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

LAP/PANEL WALL ANGLE

REVEAL DEPTH	NUMBER
NOM. 13/16"	FCP-PRM7575





A.36 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

BATTEN OSC

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-O/SCNRRVL





A.37 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

ARTISAN OSC

REVEAL DEPTH	NUMBER
1 3/8"	FCP-O/SCNR1375





A.38 PRODUCT DETAIL INSTALLATION DETAIL / Cross Section

RAIN SCREEN VENT STRIP

REVEAL DEPTH	NUMBER
NOM. 3/8"	FCP-VST375
NOM. 3/4"	FCP-VST75





A.39 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

ARTISAN ISC

REVEAL DEPTH	NUMBER
1 3/8"	FCP-I/SCNR1375





A.40 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

J-CHANNEL 1060

REVEAL DEPTH	NUMBER
NOM. 1 1/16"	FCP-J 1060





A.41 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

VERTICAL H MOLD 1060

REVEAL DEPTH	NUMBER
NOM. 1 1/16"	FCP-H 1060





A.42 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

INTEGRAL OUTSIDE CORNER 1060

REVEAL DEPTH	NUMBER
NOM. 1 1/16"	FCP-OSC 1060





A.43 PRODUCT DETAIL — INSTALLATION DETAIL / Cross Section

OUTSIDE CORNER 1060

REVEAL DEPTH	NUMBER
NOM. 1 1/16"	FCP-INTOSC 1060





VENTILATION INFORMATION



Example of vented profile with five rows of slots shown. Venting is available in one row of slots up to five rows. Specify number of rows required on your order.

USAGE

Moldings requiring venting are provided with vents for air movement. In size charts they are identified with a "V" in the center of the product number.

GUIDE SPECIFICATION

All vent slots are 1/8" wide by 1" long, spaced 11/2" on center lengthwise. Multiple rows are spaced laterally 1/2" on center. Each row of vent slots lengthwise provides approximately one square inch of vented area per lineal foot.

VENTILATION INFORMATION

REVEAL WIDTH	VENT SLOT	VENT AREA PER LINEAL FOOT APPROX.	PERCENT OF AREA VENTED APPROX.
1/2"	1	1 sq. inch	15.0%
3/4"	1	1 sq. inch	12.5%
1"	1	1 sq. inch	9.4%
1 1/2"	2	2 sq. inch	12.5%
2"	3	3 sq. inch	14.1%
3"	5	5 sq. inch	14.3%

AB.1 FIBER CEMENT PANEL REVEAL FINISHES

FINISHES

CLEAR ANODIZED FINISHES

Anodizing is an electrochemical process in which the aluminum is immersed in an acid solution through which electric current is passed. Although a natural oxidation process commences when bare, unfinished aluminum is exposed to air, producing the oxide film artificially creates a film that is thicker, harder and more durable.

GENERAL NOTE CONCERNING ANODIZED FINISHES:
Due to the nature of the anodizing process, shade variations can be expected from one element to another. This inherent characteristic of the finish need be no problem if properly anticipated in the design.

POWDER PAINT

Fry Reglet Powder paint, applied over chemical conversion coating and primer, provides durability and beauty for most interior and exterior applications. This finish is provided as the standard Fry Reglet paint finish.

This factory applied, baked-on finish is available at standard lead times in the colors shown and in custom colors to match swatches provided.

PRIME FINISH

Fry Reglet Prime Paint is spray applied in the factory and baked-on so that it serves as an ideal base for finish painting in the field.

Artic White		Autum Red	
Autumn Tan		Sable Brown	
Monterey Taupe		Hearthstone	
Mountain Sage		Suede	
Boothbay Blue		Taupe	
Cobblestone		Nantucket Gray	
Sail Cloth		Cypress	
Countrylane Red		Olive	
Evening Blue		Forest	
Sandstone Beige		Pacific Blue	
Timber Bark		Coastal Blue	
Iron Gray		Flagstone	
Traditional Red		Pewter	
Woodland Cream		Granite Gray	
Khaki Brown		Natural Clay	
Light Mist		Savannah Wicker	
Woodstock Brown		Marigold	
Rich Expresso		Light Maple	
Grey Slate		Desert Tan	
Pearl Gray		Linen	
Deep Ocean		Sterling Gray	
Aged Pewter		Snow	
Night Gray		Cedar	
Heathered Moss		Maple	
Navajo Beige		Mahogany	
Emerald		Redwood	
Slate			

FRY REGLET

800-237-9773 | www.fryreglet.com